

TopShield ELASTOMERIC SEALANT

TopShield Elastomeric Sealant is a single component, highperformance elastomeric sealant for use in a wide variety of roofing, trim, architectural metal, manufacturing, underdeck system, solar roof system, and general construction applications.

Features

ELLADOR

CONTRACT ELEMENTION

MAY SE APPLIED IN D ADVERSE CONDITIO

EXCELLENT ADHESION

& BUILDING SUR

IN EN TECHD

WARNING

CUIDADO

10.3 FL OZ (30

SELLADOR ELASTO

EXEPTIONAL ELONGATION & FLEXID

40 BE ELENGICIÓN Y FLEXIBILIDAD B

MAY BE APPLIED IN DAMP OF ADVERSE CONDITIONS

EXCELLENT ADHESION TO ROOM

& BUILDING SURFACES

DANGER!

PELIGRO!

10.3 FL OZ (304 mL)

EN APLICARSE EN COND

- Exceptional elongation and flexibility
- Excellent adhesion to many building surfaces, even when damp
- Remains flexible
- UV resistant
- Resealable, may be applied over itself
- Paintable
- Asphalt shingle composition
- Easy applied, non-stringing formulation
- Tools and cleans up easily
- Cured sealant is mildew resistant

For Use On

Asphalt shingles, coated steel (Kynar 500 based finishes), concrete, vinyl, steel, and other common roofing substrates.

CLEAR - 10.1 OZ (24 tubes/case)	TS381900
WHITE - 10.1 OZ (24 tubes/case)	TS381901
GRAY - 10.1 OZ (24 tubes/case)	TS381902
BLACK - 10.1 OZ (24 tubes/case)	TS381903
BROWN - 10.1 OZ (24 tubes/case)	TS381904
BRONZE - 10.1 OZ (24 tubes/case)	TS381905

www.srstopshield.com