



TSR-30 FEATURES

- Pneumatic nail gun or hammer installed
- Two coils of 1 3/4" nails provided
- Patented design brings you the truly functional roll out
- Compact 30 foot roll is easy to handle
- Superior weather protection and performance with no filter to clog
- Exterior convolute baffles - incurved design allows flexibility to roll up and out while maintaining its shape
- Can be cut at one foot intervals - multiple cut lines eliminates unnecessary scrap
- Patented molded fanfold end plugs - no accessories or alterations needed
- Molded centerline for fast and easy alignment
- Field tested design - proven effective under all weather conditions

- The air flow acceleration design - maximizes ventilation capacity
- Omni baffles signify air flow from any direction
- Nail holes marked every 6 inches - supported every foot - will not crush down
- Full 11 square inches of net free area per linear foot
- Engineered material guarantees longevity.
- **Lifetime Limited Warranty**

1. Compact roll for easy handling
2. Louvers close to wind stream
3. Convolute exterior baffle design
4. Innovative aerodynamic curved internal baffles
5. Unique omni baffles enhance airflow from any direction
6. Molded-In end plug



**Net Free
Area Verified**



Want more info? Scan the QR code to access additional information on TopShieldProducts.com

SPECIFICATIONS			
Model	Length (ft.)	Roof Pitch	NFA (in. ²)
TSR-30	30	2/12 to 16/12	330