



## TSLOR9-4 FEATURES

- Pneumatic nail gun or hammer installed
- Internal aerodynamic curved baffles
- External perpendicular omni baffles
- Weatherproof underlapping joint
- Four drain holes per side per foot
- 11 square inches of Net Free Area per linear foot
- External venturi baffle
- Preformed to 3/12 pitch
- Nail holes marked every 6 inches - supported every foot
- Molded nail lines
- Molded centerline for fast and easy alignment
- Alignment tabs
- External water shield

- Slot width guide lines
  - Patented molded-in fanfolded endplug fits all roof pitches
  - **Lifetime Limited Warranty**
1. Unique OmniRidge® perpendicular baffles enhance airflow
  2. Louvers positioned closer to wind stream for better air flow curved internal baffles to minimize wind resistance
  3. Aerodynamically curved internal baffles to minimize wind resistance
  4. Molded-in endplug
  5. Lo-OmniRidge® underlap prohibits weather infiltration



Want more info? Scan the QR code to access additional information on [TopShieldProducts.com](https://www.TopShieldProducts.com)

## SPECIFICATIONS

Model	Length (ft.)	Roof Pitch	NFA (in. <sup>2</sup> )	Packaged
TSLOR9-4	4	2/12 to 16/12	44	10 per box