



**Net Free
Area Verified**

TSPRO4SWN FEATURES

- Advanced low profile design
- Includes 2 ½" ring shank nails, 30 nails per piece
- Anti-rotation base design
- Internal baffles
- External "Omni" baffles
- External Venturi baffle
- "Posi-tabs" contour to shingles for improved weather protection
- Weatherproof underlapping joints
- 6 drain holes per side per foot
- 18 square inches of Net Free Area per linear foot
- 10 supported nail holes
- Preformed to 2/12 pitch
- Fits roof pitches 2/12 to 16/12
- Molded-in shingle nail lines, reinforced every 2 inches

- Slot width guide lines
 - Continuous molded end plug for improved weather protection
 - **Lifetime Limited Warranty**
1. External Venturi and "Omni" baffles provide enhanced airflow
 2. Fully supported nail holes
 3. Sonic welded fiberglass screen provides enhanced weather protection
 4. Unique "posi-tabs" contour to shingles for improved weather protection
 5. Continuous molded end plug and underlap prohibit weather infiltration



Want more info? Scan the QR code to access additional information on [TopShieldProducts.com](https://www.TopShieldProducts.com)

SPECIFICATIONS

Model	Length (ft.)	Roof Pitch	NFA (in. ²)	Packaged
TSPRO4SWN	4	2/12 to 16/12	72	10 per box