



Uncompromising Quality in Commercial Roofing



PRODUCT DATA SHEET

METAL PLATES

PRODUCT DESCRIPTION

Metal Seam Plates are used to mechanically attach single-ply and modified bituminous roof membranes to the substrate. The plate's circular design and reinforcing ribs provide exceptional strength to resist wind uplift forces. Metal Seam Plates are made of Galvalume coated steel for excellent corrosion protection that meet the requirements of ASTM D 6294, FM 4470 and DIN 50018.

Metal Insulation Plates are used to mechanically attach insulation, coverboards and BUR base sheets to the substrate. The plate's circular design and reinforcing ribs provide exceptional strength to resist wind uplift forces. Metal Insulation Plates are made of Galvalume coated steel for excellent corrosion protection.

COMPATIBLE ACCESSORIES

2" Metal Seam Plate is used within fully bonded seams to attach reinforced and non-reinforced single-ply membranes to the substrate.

2.4" Metal Seam Plates are used to attach reinforced single-ply and modified bituminous membranes to the substrate.

3" Metal Insulation Plate has a flat bottom and is used to attach roof coverboards, insulation, and BUR base sheets to the substrate.

MATERIAL SPECIFICATIONS

Manufacturing Location: Cleveland, OH USA

LEED® Eligible Recycled Content: 40%

CODE APPROVALS & LISTINGS



Size & Type	Part No.	Pkg. Qty.	Pkg. Wt.
2" Metal Seam Plate	TRUMP2000TD	1000/Bucket	27 lbs.
2.4" Barbed Metal Seam Plate	TRUMPB2400TS	1000/Bucket	52 lbs.
3" Metal Insulation Plate	TRUMP3000TS	1000/Bucket	37 lbs.



2" Metal Seam Plate

Thickness:	0.030"
Diameter:	2"
Hole Diameter:	0.260"
Coating:	AZ-55 Galvalume



2.4" Barbed Metal Seam Plate

Thickness:	0.040"
Diameter:	2.4"
Hole Diameter:	0.265"
Coating:	AZ-55 Galvalume



3" Metal Insulation Plate

Thickness:	0.017"
Diameter:	3"
Hole Diameter:	0.260"
Coating:	AZ-50 Galvalume

SRS Distribution

7440 S. Hwy 121

McKinney, TX 75070

srstopshield.com