



## #3 Asphalt Primer

### DATA SHEET

#### FOR PROFESSIONAL USE ONLY

**COMPLIANCE:** Exceeds performance requirements of ASTM D41. Miami-Dade County Product Control Approved.

**DESCRIPTION:** Use TopShield PRO #3 Asphalt Primer to prime newly laid concrete or cement decks, gypsum and masonry thermal insulation prior to applying built-up roofing. For weathered roofing, TopShield PRO #3 can be used before applying built-up roofing, black coatings or reflective coatings. TopShield PRO #3 improves adhesion.

**PREPARATION:** All surfaces must have proper drainage and be clean, dry and free of surface rust and any other foreign matter. Repair all problem areas with an approved TopShield PRO Cement. MIX THOROUGHLY. DO NOT HEAT OR THIN. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS.

**FOR BEST RESULTS:** Apply on clear sunny day when surface temperatures are between 35 °F and 120 °F. In colder weather product should be stored in heated room (65 °F to 80 °F) at least 24 hours prior to application.

**APPLICATION:** For exterior use only. Protective clothing, gloves, and eyewear should be used during application of these products. Apply with professional airless sprayer, brush or roller.

**COVERAGE RATE:** 0.25 - 1 gallon per 100 sq. ft. depending on porosity of surface and method of application. Work material to a smooth and even consistency. Avoid excessive build up or puddles of primer. DO NOT APPLY TO ASPHALT DRIVEWAYS.

**SPRAY INFO:** 100 - 500 PSI, .019 - .031 Tip Size, 0.5 - 2.0 GPM

**STORAGE & HANDLING PRECAUTIONS:** When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail.

**CLEAN-UP:** Clean tools with paint thinner or mineral spirits.

#### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	7.4 - 7.9 lbs.
Residue by Evaporation, %	60 min.
Consistency	Brush or Spray
Tack Time (50% Relative Humidity, 70 °F)	30 minutes
Full Cure (50% Relative Humidity, 70 °F)	24 - 48 hours
Application Temperatures	35 °F - 120 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

**Approx. Shipping Weights:** (Note: All approx. weights include container)

5 gallons (18.9L)	40 lbs.
55 drums (208.2L)	460 lbs.

**VOC: <350 g/L (regulatory)**

**WARRANTY AND DISCLAIMER:** SRS Distribution, Inc. (herein SRS) hereby warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any and all manufacturing defects that may materially and adversely affect the product's performance at the time the product is manufactured. Should a manufacturing defect materially and adversely affect this product's performance, SRS shall, within its sole discretion and upon receipt of Purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. THIS LIMITED WARRANTY IS PURCHASER'S SOLE AND EXCLUSIVE WARRANTY AND REPLACES ALL OTHER WARRANTIES, CONDITIONS, REPRESENTATIONS AND GUARANTEES, WHETHER EXPRESS OR IMPLIED, WHETHER BY STATUTE, AT LAW OR IN EQUITY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. This limited warranty does not cover labor or installation costs, leaks, or materials not manufactured by OEM supplier, consequential damages or incidental damages. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Direct all warranty claims in writing along with original proof of purchase to TopShield PRO, c/o Warranty Claims Department, 7440 State Highway 121, McKinney, TX 75070-2196. The exclusive venue for any legal action arising out of the purchase of this product or this warranty shall be had in a court of competent jurisdiction within Hillsborough County, Florida. Florida law shall govern. For additional Standard Limited Warranty information contact SRS at (855) 569-1550 or at [info@srstopshield.com](mailto:info@srstopshield.com).

©2021 TopShield® PRO

Manufactured For:  
SRS Distribution, Inc.  
7440 S. Hwy 121  
McKinney, TX 75070

See SDS for more information

SRS Distribution • 7440 S. Hwy 121 • McKinney, TX 75070  
Phone: 214.491.4149 • Fax: 214.491.4156 • [topshieldproducts.com](http://topshieldproducts.com)

