

### **Section 1 - Product and Company Identification**

Product Code	<b>TopShield Seam and Repair Tape – Black 6"x50'</b> Article TS-Seam06-BK Metal Roof Flashing Product APOC 4161 E. 7th Avenue
Telephone Technical <u>Emergency</u>	Tampa, FL 33605 United States 813-248-2101 800-424-9300
Last Revision Date	1/11/2018

## Section 2 - Hazards Identification

#### Signal Word – None

#### **GHS Hazards and Precautions**

The mixture does not meet the criteria for classification.

- **Prevention** Observe good industrial hygiene practices.
- **Response** Wash hands after handling.
- **Storage/Disposal** Store away from incompatible materials. Dispose of waste and residues in accordance with local authority requirements.

#### GHS Hazard Symbol – Not Required

Physical Form	-	Solid Tape
Color	-	Multiple
Odor	-	Not Identified
Flash Point	-	428°F(220°C)
OSHA(HCS2012)	-	Not classified.
WHMIS	-	Not classified.
GHS	-	Not classified.
Route Of Entry	-	Inhalation, Skin, Eye, Ingestion/Oral
Medical Conditions Aggravated by Exposure	-	Not Classified

Potential Health Effects Inhalation	
Acute (Immediate)	- Expected to be a low ingestion hazard.
. ,	
Chronic (Delayed)	- Not Classified
Skin	
Acute (Immediate)	<ul> <li>No adverse effects due to skin contact are expected.</li> </ul>
Chronic (Delayed)	<ul> <li>This product is not expected to cause skin sensitization.</li> </ul>
Eye	
Acute (Immediate)	- Direct contact with eyes may cause temporary irritation.

Chronic (Delayed) Ingestion Acute (Immediate) Chronic (Delayed) Carcinogenic Effects

- Not Classified
- Not Classified
- No data available
- This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

### Section 3 - Composition/Information on Ingredients

	Components					
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	Classifications According to Regulation/Directive	Other
Talc (Powder)	14807- 96-6	10- <20%				NDA
Other components below reportable levels	1332- 58-7	10- <90%				NDA

#### This product is an encapsulated mixture which reduces the likelihood of exposure particulates.

See Section 11 for Toxicological Information.

#### Section 4 - First Aid Measures

Inhalation	-	Move to fresh air. Call a physician if symptoms develop or persist.
Skin	-	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye	-	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	-	Rinse mouth. Get medical attention if symptoms occur.
Other Information	-	Direct contact with eyes may cause temporary irritation. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

See Section 2 for Potential Health Effects.

#### Section 5 - Fire Fighting Measures

Extinguishing Media Unsuitable Extinguishing	<ul> <li>Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).</li> <li>Do not use water jet as an extinguisher, as this will spread the fire.</li> </ul>
Media Firefighting Procedures	Use water spray to cool unopened containers. Use standard firefighting procedures
Unusual Fire and Explosion	and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.
Hazards Hazardous Combustion	During fire, gases hazardous to health may be formed.
Products Protection of Firefighters	Self-contained breathing apparatus and full protective clothing must be worn in
Flash Point	case of fire.

## Section 6 - Accidental Release Measures

Personal Precautions	-	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Emergency Procedures	-	Keep unnecessary personnel away.
<b>Environmental Precautions</b>	-	Avoid discharge into drains, water courses or onto the ground.

### Section 7 - Handling and Storage

Handling Storage Incompatible Materials or Ignition Sources	<ul> <li>Avoid prolonged exposure. Observe good industrial hygiene practices.</li> <li>Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).</li> <li>No Listing</li> </ul>
Ignition Sources	

## **Section 8 - Exposure Controls/Personal Protection**

## **Personal Protective Equipment**

Pictograms



Respiratory	<ul> <li>In case of insufficient ventilation, wear suitable respiratory equipment.</li> </ul>
Eye/Face	<ul> <li>Wear safety glasses with side shields (or goggles).</li> </ul>
Hands	- Wear appropriate chemical resistant gloves.
Skin/Body	- Wear suitable protective clothing.
General Industrial Hygiene Considerations	<ul> <li>Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.</li> </ul>
Engineering Measures/Controls	<ul> <li>Good general ventilation (typically 10 air changes per hour) should be used.</li> <li>Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.</li> </ul>
Exposure Limits/Guidelines	- Refer to listed exposure limits in state information of this section.

	Exposure Limits/Guidelines					
Result         ACGIH         NIOSH         OSHA						
				0.3 mg/m3 Total Dust		
Talc (powder)	TWAs	$2 m \sigma (m 2 T) M (A (m c m i m c h l c for c t i c m))$	2 mg/m3 TWA (respirable fraction)	0.1 mg/m3 Respirable		
CAS-14807-96-6	2 mg/m3 TWA (respirable fraction)		20 mppcf			
				2.4 mppcf Respirable		

## **Section 9 - Physical and Chemical Properties**

### **Physical Form**

Solid Rolls or Sheets -

Appearance/Description

- Various film colors, gray adhesive -

Color: Various film colors, gray	adhesive	Odor: Slight	
Taste: No data available.		Odor Threshold: NDA	
Boiling Point:	NDA	Vapor Pressure:	NDA
Melting Point:	NDA	Vapor Density:	NDA
Specific Gravity/Relative	1.04 estimated	Evaporation Rate:	NDA
Density:			
Auto-Ignition Temperature	>842 F (>450 C)	VOC (Wt.):	NDA
Bulk Density:	NDA	VOC (Vol.):	NDA

Solvent Solubility:	NDA	Flash Point:	428°F(220°C)
Viscosity:	NDA	Flash Point Test Type:	NDA

# Section 10 - Stability and Reactivity

Stability Hazardous Polymerization	<ul> <li>Material is stable under normal conditions.</li> <li>Hazardous polymerization not indicated.</li> </ul>
Conditions to Avoid Incompatible Materials	<ul> <li>Avoid temperatures exceeding the flash point. Contact with incompatible materials.</li> <li>Strong oxidizing agents.</li> </ul>
Hazardous Decomposition Products	- No hazardous decomposition products are known.

# Section 11 - Toxicological Information

Component Name	Concentration	CAS	Data
Talc (powder)	10-<20%	14807-96-6	
IARC Monographs. Overa Carcinogenicity Other Information Reproductive toxicity Specific target organ toxi single exposure Specific target organ toxi repeated exposure Aspiration hazard	city -	3 Not classifial (Talc) Prolong	arcinogenic to humans. ble as to carcinogenicity to humans. ed skin contact may cause temporary irritation. a not expected to cause reproductive or developmental effects.
Chronic effects	-	<ul> <li>Prolonged inha</li> </ul>	alation may be harmful.

Section 12 - Ecological Information		
Ecological Fate	<ul> <li>The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.</li> </ul>	
Paraiatanaa/Dagradahilitu	No date is available on the degradability of this product	

Persistence/Degradability	-	No data is available on the degradability of this product.
<b>Bioaccumulation Potential</b>	-	No data available.
Mobility in Soil	-	No data available.
Other adverse effects	-	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are

expected from this component.

## **Section 13 - Disposal Considerations**

Product	- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Packaging	<ul> <li>Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.</li> </ul>

### **Section 14 - Transportation Information**

## DOT - United States - Department of Transportation:

Shipping Name: Not Regulated as Dangerous Goods

#### IATA – International Air Transport Association:

Shipping Name: Not Regulated as Dangerous Goods

#### IMO/IMDG –International Maritime Transport:

Shipping Name: Not Regulated as Dangerous Goods

Section 15 - Regulatory Information	
SARA Hazard Classifications	- Not Classified
Risk & Safety Phrases	<ul> <li>All components are on the U.S. EPA TSCA Inventory List. This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.</li> </ul>
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	- Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	- Not regulated.
SARA 304 Emergency release notification	- Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	- Not regulated.
SARA 302 Extremely hazardous substance	- Not listed.
SARA 311/312 Hazardous	- No
SARA 313 (TRI reporting)	- Not regulated.
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	- Not regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)	- Not regulated.
Safe Drinking Water Act	- Not regulated.
US. California Proposition 65	Titanium Dioxide is listed due to its respirable nature in powder form. As supplied and applied the titanium dioxide is bound within the product matrix and is not expected to be in a respirable form. WARNING: This product contains a chemical known to the State of California to cause cancer.

State Right To Know					
Component	CAS	МА	MN	NJ	ΡΑ
Talc (powder)	14807-96-6	Yes	N/A	Yes	Yes

Section 16 - Other Information		
Last Revision Date	- 1/11/2018 - GG Inc.	
Prepared By Disclaimer/Statement of Liability		
Disclaimen/Statement of Liability	<ul> <li>This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. APOC does not accept liability for any loss or damage that may occur from the use of this information.</li> </ul>	