

DESCRIPTION:

TopShield PRO Seam & Repair Tape is self-adhesive repair and flashing tape designed to immediately stop leaks and make a variety of roofing and waterproofing repairs. Seam & Repair Tape adheres to metal, wood, structural concrete, concrete block, brick smooth BUR, smooth SBS, smooth APP, EPDM, TPO, Hypalon and PVC roofs. Application is fast, easy and clean.

PREPARATION:

Substrate should be clean, dry and free of dew, frost, oil, salt, dust and rust. Clean area first with a cloth and cleaner. On metal roofs, power wash and scrub with detergent to remove any oil or grime. Remove rust with a wire brush. Use primer on rough surfaces or in temperature below 40 °F. For best results in cold temperature application, store rolls in a warm area and warm the substrate with hot air prior to application.

APPLICATION:

Cut to length. Shorter lengths (less than 4 ft) are easier to work with unless using a team of two or more applicators. Remove release film and press in place using a gloved hand or a steel roller. Apply the exact length to predetermined location. Tape cannot be peeled up and reset. Always roll from the center out to remove trapped air pockets and fishmouths. Start in corners to eliminate "tenting". Note: For Fleece Tape, coat tape the same day with TopShield PRO silicone or acrylic coating or mastic according to product instructions, a minimum of 2" beyond tape on all sides. Coating selection will depend on existing roof type and application. Always follow manufacturer application instructions and coverage rates.

PRECAUTIONS:

TopShield PRO Tape will not adhere to silicone surfaces. For best results, test adhesion on membranes before application. Do NOT store at temperatures above 110 °F. Tape should not be stretched during installation. Presence of acidic or alkaline chemicals will reduce the life expectancy of tape and should be cleaned regularly.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Peel Strength	21 lbs. +/- in width
Application Temperature	-30 °F to 200 °F
Color	Polyester Fleece
Elongation	750%
Low Temperature Flexibility	Passes at - 65°F, no cracking
Permeability	.001 perms max
Shelf Life	5 years*
Tensile Break	800+ / -50 psi
Total Thickness	35 mils
UV Resistance	Must be coated with approved white TopShield Pro coating

*Storage at ambient room temperatures

Approx. Shipping Weights: (Note: All approx. weights include container)

4" X 50' Rolls	12 per case	50 lbs.
6" X 50' Rolls	8 per case	50 lbs.
12" X 50' Rolls	4 per case	50 lbs.

WARRANTY AND DISCLAIMER: SRS Distribution, Inc. (herein SRS) hereby warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any and all manufacturing defects that may materially and adversely affect the product's performance at the time the product is manufactured. Should a manufacturing defect materially and adversely affect this product's performance, SRS shall, within its sole discretion and upon receipt of Purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. THIS LIMITED WARRANTY IS PURCHASER'S SOLE AND EXCLUSIVE WARRANTY AND REPLACES ALL OTHER WARRANTIES, CONDITIONS, REPRESENTATIONS AND GUARANTEES, WHETHER EXPRESS OR IMPLIED, WHETHER BY STATUTE, AT LAW OR IN EQUITY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. This limited warranty does not cover labor or installation costs, leaks, or materials not manufactured by OEM supplier, consequential damages or incidental damages. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Direct all warranty claims in writing along with original proof of purchase to TopShield PRO, c/o Warranty Claims Department, 7440 State Highway 121, McKinney, TX 75070-2196. The exclusive venue for any legal action arising out of the purchase of this product or this warranty shall be had in a court of competent jurisdiction within Hillsborough County, Florida. Florida law shall govern. For additional Standard Limited Warranty information contact SRS at (855) 569-1550 or at info@srstopshield.com.